



Lumenza 4

Description:

Introducing a versatile lighting solution for effortless installation and customization. This second-generation design, with a neater look and slimmer size, features an integrated LED system with a snap-lock diffuser lens, ensuring secure and hassle-free assembly. Tailor brightness and tone with adjustable power and color temperature (CCT) to meet specific needs. Options available for this fixture include a microwave motion sensor and battery backup for added versatility.

Model: LMZ04

Optical:

| | |
|-----------------|----------|
| Lumen Efficacy: | 130 LM/W |
| LED Type: | SMD |
| CRI: | ≥80 |

Electrical:

| | |
|----------------|--------------------------|
| Input voltage: | 120-347V / 50/60HZ |
| Power : | 25W/30W/40W watt tunable |
| Beam angle: | 110° Dir Light Only |
| Power factor: | > 0.9 |

Life:

| | |
|-----------|---------|
| Lifespan: | 50,000h |
| Warranty: | 2 Years |

General:

| | |
|----------------------------|-------------------|
| Operating temperature: | 20 to 45°C |
| Finish color Availability: | White |
| Certification: | UL, CUL, FCC, DLC |

Specification:

- UL Listing:
- Suitable for damp locations
- LEDs:
- Long-life, high-efficacy, micro-power LEDs
- Lifespan:
- Lumen Maintenance, L70 > 100,000 hours
- Dimming Driver:
- Driver includes dimming control wiring for 0-10V dimming systems. The dim-to-off voltage threshold of optional 12V AUX integrated driver ranges from 0.1V to 0.5V.
- Housing:
- Sheet metal stamping



Lumenza 4

Product specification

Order guide :Example : Lumenza4-S

| Model | size | Watt Selectable | CCT Selectable | Lumen/ Watt | Voltage | Option |
|-----------|------|-----------------|-------------------|----------------|-------------|---|
| Lumenza 4 | 4FT | 25W/30W/40W | 3500K-4000K-5000K | 130lm | 120-347 VAC | Non S:Bi level sensor B:Battery back up |
| Lumenza 8 | 8FT | 55W/60W/65W | 3500K-4000K-5000K | 130lm | 120-347 VAC | |

Dimensions

