MAXTAR Lighting

Pinbeam

**ETL LISTED c US**
Intertek

Description:

Efficient and versatile, our LED Head Track Light offers precise illumination with adjustable heads. Featuring energy-saving LED technology and a sleek design, it's perfect for any space, from homes to offices

Model: STLC1511003KWHPM

Optical:

CCT:	3000K
Lumen per wattage:	80Lm/W
LED :	COB
CRI:	80Ra

Electrical:

Rated Power:	15W
Input voltage:	120V / 60HZ

Life:

Lumen maintenance:	30,000hrs
Warranty:	2 Years

General:

Dimmable Solution:	Triac
Body:	Black
Certification:	cETLus

132mm
5-1/4"

φ65mm
2-7/16"

100mm
4"

Pinbeam

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

-/+180

-150   150

-120   120

-90   0   90

100
200
-60   300   60

400   UNIT:cd

-30   500   30

0

TEST REPORT   **AAI Figure**

Flux out:1200 lm

Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

Height	Eavg,Emax		Diameter
3.281ft 1m	18.33,45.52fc 197.3,490.0lx		7.075ft 215.63cm
6.562ft 2m	4.582,11.38fc 49.32,122.5lx		14.15ft 431.26cm
9.843ft 3m	2.036,5.058fc 21.92,54.45lx		21.22ft 646.89cm
13.12ft 4m	1.145,2.845fc 12.33,30.63lx		28.3ft 862.53cm
16.4ft 5m	0.7331,1.821fc 7.891,19.60lx		35.37ft 1078.15cm

Angle:94.31deg