

### Lumenza 8









#### **Description:**

Introducing a versatile lighting solution for effortless installation and customization. This second-generation design, with a neater look and slimmer size, features an integrated LED system with a snap-lock diffuser lens, ensuring secure and hassle-free assembly. Tailor brightness and tone with adjustable power and color temperature (CCT) to meet specific needs. Options available for this fixture include a microwave motion sensor and battery backup for added versatility.

#### Model: LRL6511083CG2TO

<b>Optical:</b> Lumen Efficacy: LED Type: CRI:	130 LM/W SMD ≥80
Electrical:	
Input voltage:	120-347V / 50/60HZ
Power	55/60/65 Watt tunable
Beam angle:	110° Dir Light Only
Power factor:	> 0.9
Life:	
Lumen maintenance:	50,000h
Warranty:	2 Years
General:	
Operating temperature:	20 to 45℃
Finish color Availability:	White
Certification:	UL, CUL, FCC, DLC

#### **Specification:**

- UL Listing:
- Suitable for damp locations
- LEDs:
- Long-life, high-efficacy, micro-power LEDs
- Lifespan:
- Lumen Maintenance, L70 > 100,000 hours
- Dimming Driver:
- Driver includes dimming control wiring for 0-10V dimming systems. The dim-tooff voltage threshold of optional 12V AUX integrated driver ranges from 0.1V to 0.5V.
- Housing:
- Sheet metal stamping











### Lumenza 8



2FT	3500K	20W 4000K	5000K						
Lumens	2600	2620	2640	1					
Efficacy (Im/W	130	131	132						
3FT		25W							
Lumens	3500K	4000K	5000K						
Efficacy (Im/W	3250	3275	3300			. //			
	130	131	132						
4FT		30W			35W			45W	
Lumens	3500K	4000K	5000K	3500K	4000K	5000K	3500K	4000K	5000K
Efficacy (Im/W)	3900	3930	3960	4550	4585	4620	5850	5895	5940
	130	131	132	130	131	132	130	131	132
8FT		65W			75W			90W	
Lumens	3500K	40001	< 5000K	3500K	4000K	5000K	3500K	4000K 5	5000K
Efficacy (Im/W)	8450	8515	8580	9750	9825	9900	11700	11790 1	11880
	130	131	132	130	131	132	130	131	132

Ordeı	ring table		Sample : LRLG2-4-40-347-3C-W			
Modle	Lengh Wattage		Voltage	ССТ	Options	
LRLG2	2ft :2 3ft :3 4ft: 4 8ft: 8	20W:20 25W:25 28W-32W-40W :40 55W-60W-65W: 65	120-277:UNV 120-347 : 347	3CCT : 3C	Battery : B Sensor : S Wire guard : W	





# Lumenza 8



#### **DIMANSION:**







# PRODUCT WEIGHT(Kg/lb.)

