

















Description:

The Aero Beam is a high-performance area light engineered for versatility and efficiency across a wide range of outdoor applications. Available in three power categories with watt-selectable options, it covers outputs from 60W up to 500W, making it ideal for everything from small parking lots to large commercial sites.

Designed for total flexibility, Aero Beam offers multiple control options, including built-in and plug-in dusk-to-dawn sensors as well as Zhaga-compatible smart sensors for advanced lighting control. It is available with four precision optical distributions and seven mounting configurations, ensuring perfect adaptability to any site condition.



Model: AB10

Optical:

CCT: 3CCT(3000/4000/5000K) Lumen Efficacy: 130LM / W(5000KRa70)

LED Type: SMD2835 CRI: Ra>80

Electrical:

Rated Power: 150W-300W/500W 5 Wattages Selectable Input voltage: AC120-277V & AC120-347V & AC277-480V

THD: <20%
Power factor: >0.90

Life:

Lifespan: 50,000hrs Warranty: 2 Years



Dimmable Solution: (0 -10V)
IP: IP65

Housing: Die-cast Aluminum

Finish color Availability: Bronze(Standard), Custom finishes available

Certification: UL/cUL, DLC 5.1 Premium



















500W











AC277-480V

AC120-277V

AC120-347V

AC277-480V

0-10V

CRI>80

80000lm@500W







T3, T4

(Default T3)



Areo Beam

AB10-500

Performance Summary

Model NO. #	Watts	ССТ	LPW	Lumens(±10%)	Voltage	DIM	CRI	Beam Angle
AB10-150S	150/120/100/80/60W Selectable	CCT Selectable	162 lm/W	23168lm@150W	AC120-277V 0-10		V 051 00	Optic Swap T2/T3/T4;
AB10-300S	300/240/200/180/150W Selectable	3000K 4000K 5000K	163 lm/W	46078lm@300W	AC120-347V AC277-480V	0-10 v	CRI>80	(Default T3); T5 lens optional
	T	ССТ						
AB10-500S	500/450/400/350/300W Selectable	Selectable 3000K	163 lm/W	76393lm@500W	AC120-277V AC120-347V	0-10V	CRI>80	T3, T4 (Default T3)

5000K

Single CCT

4000K

5000K

Lumen Output (3CCT Selectable)

500W

Model #	Size	Voltage	Wattage	ССТ	Lumens(Im)	Efficiency(Im/W)
				3000K	21,620	146.3
			150W	4000K	23,168	162.5
				5000K	23,130	154.4
			120W	3000K	17,715	152.9
				4000K	18,729	166.6
				5000K	18,545	159.1
			100W	3000K	15,767	157.1
AB10-150S	15"	120-277V		4000K	16,457	168.7
AB 10-1300				5000K	16,399	162.7
				3000K	12,692	160.5
			80W	4000K	13,242	171.3
				5000K	13,310	167.5
			60W 3000K 4000K	3000K	9,687	164.3
				4000K	10,031	173.3
				5000K	10,152	171.5
				3000K	43,019	146.0
			300W	4000K	46,078	163.2
				5000K	45,684	153.6
A D 40 0000	22"	120-277V		3000K	36,311 152.1	152.1
AB10-300S		120 2777	240W	4000K	38,432	167.0
				5000K	37,806	157.5
				3000K	31,017	156.4
			200W	4000K	32,557	169.6
				5000K	32,320	162.2

160 lm/W













Model #	Size	Voltage	Wattage	ССТ	Lumens(Im)	Efficiency(Im/W)
	22"	120-277V	180W .	3000K	28,443	159.0
				4000K	29,607	170.9
AB10-300S				5000K	29,531	164.5
1.210 0000			150W	3000K	24,180	160.6
				4000K	25,158	172.3
				5000K	25,307	168.3
				3000K	70,120	144.6
			500W	4000K	76,393	163.1
				5000K	76,001	154.8
				3000K	65,058	148.0
			450W	4000K	69,903	164.9
	24"			5000K	67,933	154.3
		120-277V	40014/	3000K	59,347	151.9
AB10-500S			400W 350W	4000K	63,645	168.0
				5000K	64,210	161.4
				3000K	53,297	155.3
				4000K	56,589	169.8
				5000K	55,640	161.8
			300W	3000K	47,033	158.7
				4000K	49,620	172.0
				5000K	49,063	165.4
	24" 1	120-277V	500W	5000K	82,227	168.9
			450W	5000K	74,717	168.8
AB10-500			400W	5000K	67,985	171.0
			350W	5000K	61,097	173.9
			300W	5000K	52,823	176.3





















Mounting Bracket (Sold separately)

Picture	Item #	Description		
•	ACC-SB01-SF01-BZ-NMB	Mounting Bracket, Slip Fitter(SF), Bronze finish		
6	ACC-SB01-DI02-BZ-NMB	Mounting Bracket, Direct Mount(DI), Bronze finish		
6	ACC-SB01-UDI01-BZ-NMB	BB01-UDI01-BZ-NMB Mounting Bracket, Universal Direct Mount(UDI), Bronze finish		
	ACC-SB01-SR01-BZ-NMB	Mounting Bracket, Square/Round Pole Bracket(SR), Bronze finish		
	ACC-SB01-YM01-BZ-NMB	Mounting Bracket, Yoke Mount(YM), Bronze finish		
	ACC-SB10-TR01-BZ-NMB-150W	Mounting Bracket, Trunnion Mount(TR) for 150W & 300W, Bronze finish		
	ACC-SB10-TR01-BZ-NMB-500W	Mounting Bracket, Trunnion Mount(TR) for 500W, Bronze finish		
	ACC-SB10-U01-BZ-NMB-150W	Mounting Bracket, U Bracket(U) for 150W & 300W, Bronze finish		
	ACC-SB10-U01-BZ-NMB-500W	Mounting Bracket, U Bracket(U) for 500W, Bronze finish		

Accessories (Sold separately)

Picture	Item #	Description		
	ACC-SB10-P	Built-in Photocell for 150W & 300W		
	ACC-SB10-L-T5	T5 lens for 150W & 300W		
-	ANT-5-4T	Sharkward Plug-in Microwave Motion Sensor		
7	ANT-5-4T-BLE-GE	Sharkward Plug-in Bluetooth Microwave Motion Sensor		
	ANT-5-ZT	Sharkward Zhaga Microwave Motion Sensor		
	ANT-5-ZT-BLE-GE	Sharkward, Zhaga Bluetooth Microwave Motion Sensor		
	OJ-M715-B	Ojun 3 Pin Photocell		
	ZYS-P20M ZYS-P10M ZYS-P10A	ZYS-P20M, 20KV Surge Protector for AC120-347V ZYS-P10M, 10KV Surge Protector for AC120-347V ZYS-P10A, 10KV Surge Protector for AC120-277V		
	RC-100	Sharkward Remote Controller		

















Dimensions



Dimension for Mounting Bracket


















Photometry


150W -T2 Type: 60W 4000K





150W -T3 Type: 60W 4000K






















Photometry


150W -T4 Type: 60W 4000K





150W -T5 Type: 60W 4000K




















Photometry


300W -T2 Type: 150W 4000K





300W -T3 Type: 150W 4000K

























300W -T4 Type: 150W 4000K





300W -T5 Type: 150W 4000K























Photometry

500W -T3 Type: 300W 4000K





500W -T4 Type: 300W 4000K

