



LED Linear High Bay Light

Description:

B40 features an IP65-rated waterproof light engine, ensuring stable performance while minimizing costs. With versatile optics, CCT & wattage selectable, and plug & play sensor, it's perfect for shopping centers, supermarkets, warehouses, factory production areas, and aisles.




Model: HYL300B40112CWHAG

Optical:

CCT: 2CCT Selectable 4000K-5000K
 Lumens : 13500 to 45000lumens
 LED Type: LED 2835
 CRI: Ra80

Electrical:

Rated Power: 90W to 300W
 Input voltage: 100-277VAC, 120-347VAC , 277-480VAC
 Beam angle: 60°/85°/105° selectable
 Power factor: >0.95
 Control: ON/OFF, Microwave ,PIR sensor







Life:

Lumen maintenance: @Ta=25° 100800hrs-L80
 160800hrs-L70
 Warranty: 5 Years
 Operating Temperature °C/°F -30° to+50°/ -22° to +122°

General:

Dimmable Solution: NA
 IP: IP65
 IK: 08
 Finish color Availability: White
 Applications: Warehouse /Industrial facility /Exhibition center
 Shopping Mall / Gymnasium /Toll Station






LED Linear High Bay Light


Specification

Model No	Size(mm)	Watt(W)	CCT(K)	CRI	LPW @5000K Ra80	Lumens (lm)	Voltage (Vac)	Beam Angle
B40-150WS	333X253X102	150/120/90 Selectable	4000,5000 Selectable	80	150	Up to 22500	120-277 120-347 277-480	30x100° 60x100° 80x100° 110°
B40-300WS	663X253X117	300/240/180 Selectable	4000,5000 Selectable	80	150	Up to 45000	120-277 120-347 277-480	30x100° 60x100° 80x100° 110°


Different installation



Suspend with cable



Suspend with Rod



Surface mount




LED Linear High Bay Light

2 CCT selectable

Die-casting aluminum housing



3 wattage selectable



2 sizes ranging from 90W to 300W



IP65 light engine to prevent damp, bugs, dust, and LED damage

Plug-and-play sensor:
Microwave sensor, PIR sensor


Mounting Option



Suspension Mounting



Pendant Mounting



Surface Mounting



LED Linear High Bay Light

Accessories



Suspension rope
Code: SL-L09-01



Surface mounting bracket
Code: BC-L40-01



Pendant mounting bracket
Code: BC-L40-02



Microwave sensor
Code: SR-H30-01



PIR sensor
Code: HN074-01VRPH







CASAMBI ready wireless controller
Code: UP-CN01



Remote controller
Code: HD05R

Photometry





LED Linear High Bay Light

Dimensions

