

# IG04

## IN GROUND LED LIGHT




### DIMENSIONS



### SPECIFICATIONS

<b>Model No.</b>	IG-04
<b>Power Consumption(±10%)</b>	2W
<b>Input Voltage</b>	24VDC
<b>Correlated Color Temperature</b>	3000K/6000K
<b>Dimming</b>	0-10V/TRIAC/DALI/PWM
<b>Beam Angle</b>	25°
<b>Product Dimension</b>	43×58Ømm
<b>Mounting Option</b>	Recessed in ground
<b>Material</b>	Stainless steel cover, die-casting aluminum body, tempered frosted glass
<b>Fixture Color</b>	Grey powder coated
<b>IK Rating</b>	IK08
<b>IP Rating</b>	IP67
<b>Operating Temperature</b>	-20°C to + 40°C
<b>Life Time of LED @Ta=25°C</b>	50000 Hours
<b>Warranty</b>	3 Years
<b>Application</b>	Outdoor, landscape, pathway

### DISTRIBUTION



Lux distance curve

Center beam LUX	Beam width V	Beam width H
2m 101.90LUX	0.9m	0.9m
4m 25.48 LUX	1.8m	1.8m
6m 11.32 LUX	2.7m	2.6m
8m 6.37LUX	3.6m	3.5m
10m 4.08LUX	4.5m	4.4m
12m 2.83 LUX	5.4m	5.3m

Ver.Spread:25.3 Horiz.Spread:24.7

