

Slimore SPECIFICATION SHEET





#### **Description:**

Introducing our LED Wall Pack: Designed with a slim profile to minimize space while delivering an impressive 125 lumens per watt. Enhance the modern aesthetic of your commercial or residential building facade with this sleek lighting solution. Easy installation on standard electrical junction boxes makes this product a convenient choice for any application. Illuminate your space efficiently and stylishly with our LED Wall Pack.

Model:	WI	LP05X	<b>X11X</b> )	XKAG
model.	**	05/	/\ I I/\/	$\cdots$

Optical:

CCT: 5000K (4000K optional)

Lumen Efficacy:125LM/WLED Type:LED 3030CRI:Ra70



#### **Electrical:**

Rated Power: 12W / 25W / 30W / 40W / 70W Input voltage: 100-277 VAC 50 / 60 Hz

Beam angle: U04201 / R08401
Power factor: ≥0.9 at Max Load

Life:

Lifespan: 48,000hrs Warranty: 2 Yaers

General:

Dimmable Solution: N/A IP: IP66 IK: IK08

Operating temperature: -30°C to + 45°C
Material: Cast Aluminum
Finish color Availability: Powder Coating
Fixture Color: Sliver gray

Certification: cETLus

Application: Security / Pathway and Perinneter lighting / Building

facdes









Slimore

**SPECIFICATION SHEET** 




## **DIMENSIONS**






### **PHOTOMETRY**

# 12W/25W/30W



U04201

## 40W/70W



R08401