




OWL09

OUTDOOR WALL LIGHT SPECIFICATIONS



Job Information	
Project Name	
Type	
Location	
Quantity	
Date	



Lux distance curve

Center beam LUX	Beam width	
	V	H
2m	1421.67 LUX	0.9m 0.9m
4m	355.42 LUX	1.8m 1.8m
6m	157.96 LUX	2.6m 2.7m
8m	88.85 LUX	3.5m 3.5m
10m	56.87 LUX	4.4m 4.4m
12m	39.49 LUX	5.3m 5.3m

Ver.Spread:24.8 Horiz.Spread:24.9

DESCRIPTION

The OWL-9 is a high-quality outdoor wall light designed for down illumination, perfect for wet locations and exterior applications. Crafted with a durable extruded aluminum alloy#6063 body and finished in Black, Dark Grey, or Silver Grey, it offers low-glare performance with a sleek modern look.

The fixture features prime powder coating with excellent adhesion, meeting ISO Class 1 / ASTM Class4B standards, ensuring long-lasting durability and weather resistance.

PERFORMANCE

MODEL NAME	OWL09
POWER CONSUMPTION(±10%)	18 W
INPUT VOLTAGE	24VDC/110-277VAC
LUMINOUS FLUX (±10%)	1620 LM
EFFICACY(4000K RA80)	90 LM/W
CCT	3000K/6000K
CRI	>80
MATERIAL	EXTRUDED ALUMINUM
FINISH	BLACK/DARK GREY/SILVER GREY
DIMENSIONS	195.5x140x100mm(7.7"x5.5"x3.9")
IP RATING	IP65
IK RATING	IK10
OPERATING TEMPERATURE	-20°C TO + 55°C(-4°F TO 131°F)
LIFESPAN OF LED @TA=25°C	50000HRS
WARRANTY	5 YEARS

PRODUCT ORDERING GUIDE

EXAMPLE: OWL09-24-18-3000-N-G

SERIES	VOLTAGE-WATTAGE(W)	CCT	DIMMING	FINISH
OWL09	24-18: 24VDC, 18W	3000	T: TRIAC	G: DARK GREY
	UNV-18: 110-277VAC, 18W	6000	V: 0-10V	B: BLACK
			N: NONE	S: SILVER