


PL02

PENDANT LINEAR LIGHT SPECIFICATIONS



| Job Information | |
|-----------------|--|
| Project Name | |
| Type | |
| Location | |
| Quantity | |
| Date | |

DESCRIPTION

PL02 is a minimalist pendant linear fixture engineered for direct illumination—ideal for commercial interiors and workspace environments. Its design balances clean aesthetics with performance, delivering uniform, visually comfortable light in demanding interior settings. The linkable design features a seamless prismatic diffuser, which can be ordered in roll format to ensure smooth, continuous light lines across multiple fixtures.

OVERVIEW

- Linkable direct linear light
- Simple, easy and quick installation
- Efficient lighting up to 130 LM/W
- Flexible prismatic diffuser
- UGR<19 provides visual comfort

PERFORMANCE


| | |
|---------------------------|---------------------------------|
| MODEL NAME | PL02 |
| POWER CONSUMPTION(±10%) | 30W 40W |
| LUMINOUS FLUX | 3600 LM 4800 LM |
| EFFICIENCY | UP TO 130 LM/W |
| INPUT VOLTAGE | 120-277VAC |
| POWER FACTOR | ≥0.9 |
| DIMMING | 0-10V |
| CCT | 3000K/3500K/4000K/6000K |
| CRI | >80 |
| UGR LEVEL | <19 |
| BEAM ANGLE | 90° |
| MOUNTING OPTIONS | PENDANT |
| FINISH | SILVER/WHITE/BLACK |
| IP RATING | IP20 |
| OPERATING TEMPERATURE | -20°C TO + 45°C (-4°F TO 113°F) |
| LIFE TIME OF LED @TA=25°C | 50000 HRS L80 |
| WARRANTY | 5 YEARS |
| APPLICATIONS | INDOORS |

PRODUCT ORDERING GUIDE

EXAMPLE: PL02-30W-3000-V-S

| SERIES | WATTAGE | CCT | DIMMING | FINISH |
|--------|---------|------|----------|-----------|
| PL02 | 30W | 3000 | V: 0-10V | B: BLACK |
| | 40W | 3500 | N: NONE | S: SILVER |
| | | 4000 | | W: WHITE |
| | | 6000 | | |

DIMENSIONS



FEATURES

► Optics

Downward (direct) illumination

► Electrical

Voltage 120-277VAC

► Environment & Certifications

cETL listed for dry locations

► Warranty

5 years limited warranty

► Mounting

Pendant linkable.

► Finish

The powder-coated finish ensures a uniform appearance, offering long-term durability and superior aesthetics.

► Housing Material



Die-cast aluminum housing ensures durability and efficiency, with heat resistance polycarbonate lens.

► LED System

CRI With a 80+ color rendering index (CRI), this product delivers outstanding illumination, featuring tight chromatically specifications and a precise color binning process to ensure consistency in CRI and CCT.

CCT Available in 3000K, 3500K, 4000K and 6000K with excellent color consistency.

DISTRIBUTION



PL02

PENDANT LINEAR LIGHT SPECIFICATIONS

