

## Double Multiple ceiling light

### SPECIFICATIONS



Performance	EM-GRGU102HBK-LH
Efficiency	70lm/W
Bulb	GU10
CCT	3000/4000/5000 K
CRI	Ra>80
Voltage	120-277
Wattage	16W

### Operating Condition

Operating Temperature	-20~+40 C
Storage Temperature	-40~+85 C

### DIMENSIONS

Width: 9.35", Length: 5", Height: 5"

### DESCRIPTION Mini LED Multiple Spots for remodeling and new construction application for residential and commercial

The Multiple Spots are marketed as complete units including the housing and trim. Available as One, two and three-light configurations, each spot is individually. Adjustable and provides a 30-degree visual cut off for glare control.

### FEATURES Individually adjustable luminaries

Complete unit includes housing & trim  
 All housings are Non-IC rated  
 30° vertical tilt, 360° horizontal rotation  
 Die-cast aluminum heat sink painted black. Trim and housing are constructed of Gauge Steel.  
 Supplied with 4 ways hanger bar, adjustable from 14½"-25" to accommodate various joist construction and grid sizes.  
 Hanger bars include a captive mounting "screw-nail" for ease installation. Can be accommodate a 1/2" to 1 1/4" ceiling thickness. Dimmable to 10% with most brand dimmers

